AIP GERMANY

AD 2 EDDP 5-7-17

Effective: 19 NOV 2009

STANDARD DEPARTURE ROUTES – INSTRUMENT RNAV (GPS) - SID

LEIPZIG/HALLE RWY 26L

	Route	After Take-Off		
Designator		Climb to	Contact	Remarks
1	2	3	4	5
LELMA 1S	LELMA ONE SIERRA Climb on track 264° to DP520 or 900, whichever is later, RT, via DP521 on track 004° to ETIPO (△), RT, on track 081° to DP522, RT, on track 090° to LELMA (△). MAX IAS 210 kt until established on track 004° to ETIPO. GPS/FMS RNAV: [A900+] - DP520[A900+; R] - DP521[K210-] - ETIPO[R] - DP522[R] - LELMA.	FL 70	München Radar 126.175	
UMBAL 1S	UMBAL ONE SIERRA Climb on track 264° to DP520 or 900, whichever is later, RT, via DP521 on track 004° to ETIPO (△), RT, on track 016° to UMBAL (△). MAX IAS 210 kt until established on track 004° to ETIPO. GPS/FMS RNAV: [A900+] - DP520[A900+; R] - DP521[K210-] - ETIPO[R] - UMBAL.			Only available between 2200 (2100) and 0500 (0400). No access to (U)Z20.

Notes: Attention departing aircraft: Simultaneous parallel departures in progress. Pilots have to proceed exactly on extended centreline until starting turns as published in departure routes and shall remain on TWR frequency until further advised.

(DP520 fly-over way point)

Contact München Radar when advised by Tower!