AIP GERMANY

AD 2 EDDP 5-7-5 Effective: 19 NOV 2009

STANDARD DEPARTURE ROUTES – INSTRUMENT RNAV (GPS) - SID

LEIPZIG/HALLE RWY 08L

Designator	Route	After Take-Off		
		Climb to	Contact	Remarks
1	2	3	4	5
NAMUB 2Q	NAMUB TWO QUEBEC On RWY track to DP537 or 900, whichever is later, RT, via DP538 on track 198° to DP539, RT, on track 236° to DP548, LT, on track 211° to DP540, RT, on track 211° to DP540, RT, on track 268° to NAMUB (△). MAX IAS 210 kt until DP539. Cross DP540 at or above 5000. GPS/FMS RNAV: DP537 - [A900+; R] - DP538[K210-] - DP539[K210-; R] - DP548[L] - DP540[A5000+; R] - NAMUB.	FL 70	München Radar 126.175	Only available between 0500 (0400) and 2100 (2000). Only available for ACFT with less than 136 t MTOM. If unable to comply, file NAMUB 1H.

Notes: Attention departing aircraft: Simultaneous parallel departures in progress. Pilots have to proceed exactly on extended centreline until starting turns as published in departure routes and shall remain on TWR frequency until further advised.

(DP537 fly-over way point)

Contact München Radar when advised by Tower!