

KERRY STANDARD INSTRUMENT DEPARTURES RWY 08

AIRCRAFT CATEGORIES C

Where climb instructions to levels higher than the maximum SID altitude are issued by ATC, Pilots, **unless specifically instructed to the contrary**, must comply with all tracks, minimum level and all indicated airspeed restrictions specified in the SID.

ATS Route	SID Designator	Routeing	Altitude
Shannon	SHA 1C	Climb on KER NDB QDR 078 to 5D IKR. Turn left, intercept RDL 216 inbound to SHA VOR.	Climb 4000ft Maintain minimum 4.0% climb to MSA. Cross 5D IKR 1300ft or above. Cross 33D SHA 2200ft or above.
Cork	CRK 1C	Climb on KER NDB QDR 078 to 5D IKR. Turn right, intercept RDL 312 inbound to CRK VOR.	Climb 4500ft Maintain minimum 4.0% climb to MSA. Cross 5D IKR 1300ft or above. Cross 35D CRK 2500ft or above
All routes	KER 1C	Climb on KER NDB QDR 078 to 5D IKR. Turn right onto track 312 to KER NDB.	Climb 4000ft Maintain minimum 4.0% climb to MSA. Cross 5D IKR 1300ft or above. Cross KER NDB 4000ft. From KER NDB, climb if necessary, in KER NDB holding pattern (See chart EIKY AD 2.24-10) to MSA before setting course.