



CHANGE: CLASSIFICATION OLBIA CTR MODIFIED

PROCEDURA DI SALITA INIZIALE RWY 30

Dopo il decollo virare a destra prima possibile su rotta 120°, mantenendo VMC fino a lasciare la costa (QDR 005° ARB L). Attraversando 2000 ft, se autorizzati via:

- a. **SID VAVAX 5D**
Virare a destra per ARB L da raggiungere a 5000 ft o più.
Minimo rateo di salita: 5.5% (330 ft/NM).
- b. **SID QUENN 5B**
Virare a sinistra fino ad intercettare e seguire QDR 069° ARB L.
Minimo rateo di salita: 5.5% (330 ft/NM) fino a lasciare 2000 ft.
- c. **SID ALEDI 6B**
Virare a destra fino ad intercettare e seguire QDR 141° ARB L.
Minimo rateo di salita: 5.5% (330 ft/NM) fino a lasciare 2000 ft.

DESCRIZIONE DELLE SID**VAVAX 5D**

Lasciare ARB L su QDR 351° (RDL 171 SME VOR) diretti al punto VAVAX.

Minimo rateo di salita: 5.5% (330 ft/NM) fino a lasciare 7000 ft.

MCL: RDL 171/44 NM SME VOR/DME FL 100.

QUENN 5B

Seguire QDR 069° ARB L diretti al punto QUENN.

MCL: QUENN FL 90

ALEDI 6B

Seguire QDR 141° ARB L diretti al punto ALEDI.

MCL: ALEDI FL 90

INITIAL CLIMB PROCEDURE RWY 30

After take-off turn right as soon as possible on track 120°, maintaining VMC till leaving coast-line (QDR 005° ARB L). Passing 2000 ft, if cleared via:

- a. **SID VAVAX 5D**
Turn right bound to ARB L to be reached at 5000 ft or above.
Minimum rate of climb: 5.5% (330 ft/NM).
- b. **SID QUENN 5B**
Turn left until joining QDR 069° ARB L.

Minimum rate of climb: 5.5% (330 ft/NM) until passing 2000 ft.
- c. **SID ALEDI 6B**
Turn right until joining QDR 141° ARB L.

Minimum rate of climb: 5.5% (330 ft/NM) until passing 2000 ft.

SID DESCRIPTION**VAVAX 5D**

Leave ARB L on QDR 351° (RDL 171 SME VOR) bound to VAVAX.

Minimum rate of climb: 5.5% (330 ft/NM) until passing 7000 ft.

QUENN 5B

Follow QDR 069° ARB L bound to QUENN.

ALEDI 6B

Follow QDR 141° ARB L bound to ALEDI.

Intenzionalmente bianca

Intentionally left blank