

STANDARD DEPARTURE
ROUTES – INSTRUMENT
(SID)

ALLENDORF/EDER
RWY 11/29

| Designator | Route | After Take-Off | | Remarks |
|---|---|----------------|-------------------------|--|
| | | Climb to | Contact | |
| 1 | 2 | 3 | 4 | 5 |
| RWY 11 | | | | |
| OHMAR 2V | OHMAR TWO VICTOR Climb on RWY track to 5100 or above; RT, on track 174° to OHMAR (Δ). Climb with 10.0% (608 ft/NM) until passing 5100. GPS/FMS RNAV: [A1600+] - FQ111[A5100+; R] - OHMAR. | FL70 | Langen Radar 124.725 | 1. Not to be used during activity of NLFS. 2. PDG 10.0% (608 ft/NM) due to air-space structure. If unable to comply, advise ATC. 3. After 5100 BRNAV equipment necessary. |
| KULIX 2V | KULIX TWO VICTOR Climb on RWY track to 2400 or above; LT, on R202 WRB to 28.7 DME WRB; LT, on track 305° to KULIX (Δ). Climb with 12.0% (729 ft/NM) until passing 5800. Cross 28.7 DME WRB at 5800 or more. GPS/FMS RNAV: [A1600+] - FQ110[A2400+; L] - FQ112 - FQ114[A5800+; L] - KULIX. | | | 1. Not to be used during activity of NLFS. 2. PDG 12.0% (729 ft/NM) due to airspace structure. If unable to comply, advise ATC. 3. After 28.7 DME WRB BRNAV equipment necessary. |
| WRB 2V | WARBURG TWO VICTOR Climb on RWY track to 2400 or above; LT, on R202 WRB to WRB (Δ). Climb with 10.0% (608 ft/NM) until passing 4000. GPS/FMS RNAV: [A1600+] - FQ110[A2400+; L] - FQ112 - WRB. | | | 1. Not to be used during activity of NLFS. 2. PDG 10.0% (608 ft/NM) due to navaid coverage. |
| (Sample: <u>FQ110</u> fly-over way point) | | | | |
| RWY 29 | | | | |
| OHMAR 2C | OHMAR TWO CHARLIE Climb on RWY track to 5800 or above; LT, on track 129° to OHMAR (Δ). Climb with 10.0% (608 ft/NM) until passing 5800. GPS/FMS RNAV: [A1600+] - FQ291[A5800+; L] - FQ294 - OHMAR. | FL70 | Langen Radar 124.725 | 1. Not to be used during activity of NLFS. 2. PDG 10.0% (608 ft/NM) due to airspace structure. If unable to comply, advise ATC. 3. PDG 10.0% (608 ft/NM) up to 2400 due to obstacle. 4. After 5800 BRNAV equipment necessary. |
| KULIX 2C | KULIX TWO CHARLIE Climb on RWY track to 5800 or above; RT, on track 330° to KULIX (Δ). Climb with 10.0% (608 ft/NM) until passing 5800. GPS/FMS RNAV: [A1600+] - FQ292[A5800+; R] - KULIX. | | | |
| WRB 2C | WARBURG TWO CHARLIE Climb on RWY track to 2400 or above; RT, on R215 WRB to WRB (Δ). Climb with 10.0% (608 ft/NM) until passing 4000. GPS/FMS RNAV: [A1600+] - FQ290[A2400+; R] - FQ296 - WRB. | | | 1. Not to be used during activity of NLFS. 2. PDG 10.0% (608 ft/NM) up to 4000 due to navaid coverage. 3. PDG 10.0% (608 ft/NM) up to 2400 due to obstacle. |
| (Sample: <u>FQ291</u> fly-over way point) | | | | |