

STANDARD DEPARTURE
ROUTES – INSTRUMENT
(SID)

EMDEN
RWY 07/25

Designator	Route	After Take-Off		Remarks
		Climb to	Contact	
1	2	3	4	5

RWY 07

JUIST 1P	JUIST ONE PAPA On track 072° to WE400; LT, via WE401 on track 306° to JUIST (Δ). RNAV(GPS): [A400+] - WE400[L] - WE401 - JUIST.	3000 ft	Wittmund/Jever Radar 123.600 Bremen Radar 120.225/124.800	For helicopter only.
EMPIT 1P	EMPIT ONE PAPA On track 072° to WE402; RT, via WE403 on track 147° to EMPIT (Δ). RNAV(GPS): [A400+] - WE402[R] - WE403 - EMPIT.	5000 ft		Not to be used during activity of NLFS.

RWY 25

JUIST 1G	JUIST ONE GOLF On track 252° to WE300; RT, on track 317° to JUIST (Δ). RNAV(GPS): [A400+] - WE300[R] - JUIST.	3000 ft	Wittmund/Jever Radar 123.600 Bremen Radar 120.225/124.800	For helicopter only.
EMPIT 1G	EMPIT ONE GOLF On track 252° to WE301; LT, via WE302 on track 115° to EMPIT (Δ). 3.7% (230 ft/NM) until passing 1000. RNAV(GPS): [A400+] - WE301[L] - WE302 - EMPIT.	5000 ft		<ol style="list-style-type: none"> Not to be used during activity of NLFS. PDG 3.7% (230 ft/NM) due to obstacles.

(Sample: WE400 fly-over way point)

Contact Bremen Radar immediately after take-off!